



New ECOMETER for 10 - 12 t axles with ECO Plus 3

75262301e
2023-03-01

With the series introduction of ECO Plus 3 bearing technology in the axle load range of 10 - 12 t, new variants of the BPW ECOMETER are also being introduced. The new hub cap with integrated hubodometer has a threaded connection of M 135 x 2 and is mounted with an O-ring. The tightening torque of the hub cap is now only 350 Nm and is therefore more service-friendly.



The new ECOMETER for 10 - 12 t axles is available in the following versions:

ECO Plus 3 M 135 x 2 with O-ring	Rolling circumference in mm	Tyre size for example
05.212.75.52.0	2170	205/65 R 17.5
05.212.75.53.0	2350	215/75 R 17.5
05.212.75.54.0	2425	235/75 R 17.5 245/70 R 17.5
05.212.75.55.0	2560	9,50 R 17,5 8.25 R 15 245/70 R 19.5
05.212.75.56.0	2620 - 2650	265/70 R 19.5
05.212.75.57.0	2712 - 2750	285/70 R 19.5
05.212.75.58.0	2730 - 2790	445/45 R 19.5
05.212.75.46.0	2830 - 2860	255/70 R 22.5
05.212.75.47.0	2915	275/70 R 22.5
05.212.75.59.0	2960	425/55 R 19.5
05.212.75.48.0	3015 - 3134	315/70 R 22.5
05.212.75.49.0	3175 - 3220	10.00 R 20 11.00 R 22.5
05.212.75.50.0	3240 - 3260	385/65 R 22.5
05.212.75.51.0	3280 - 3310	12.00 R 22.5 365/80 R 20
05.212.75.60.0	3410 - 3470	425/65 R 22.5 13.00 R 22.5
05.212.75.61.0	3505	445/65 R 22.5

Note: The ECOMETER for 9 t axles with ECO Plus 3 cannot be used with the new 10 to 12 t axles with ECO Plus 3 due to their lower overall height.

For further information, please contact your BPW representative.