

# BPW ECO Wheel

Forged for more economy.



we think transport



# Product overview BPW ECO Wheel

Forged aluminium wheels for increased economy with KBA approval for all wheel sizes.

**5 YEAR WARRANTY**  
WITHOUT KILOMETRE LIMIT\*

WHEEL SIZE	RECOMMENDED TYRE SIZE	SURFACE	OFFSET (MM)	HALF CENTRE DISTANCE (MM)	BOLT HOLE DIAMETER (MM)	MAXIMUM WHEEL LOAD (KG)	WEIGHT (KG)	WHEEL CONNECTION	KEY THICKNESS (MM)	TWIN ASSEMBLY	USE	BPW CODE NUMBER
22,5 x 11,75	365/70 R22,5; 385/65 R22,5; 385/55 R22,5; 15 R22,5	brillant	120	–	32	5000	26,2	281/335/10	27	no	Truck & Trailer/semitrailer	02.3511.43.12
					26		26,4					02.3511.44.12
		highly polished	120	–	32	5000	26,2	281/335/10	27	no	Truck & Trailer/semitrailer	02.3511.45.12
					26		26,4					02.3511.46.12
		brillant	0	–	32	4500	22	281/335/10	23	no	Trailer/semitrailer	02.3511.47.12
					26		22,2					02.3511.48.12
		highly polished	0	–	32	4500	22	281/335/10	23	no	Trailer/semitrailer	02.3511.49.12
					26		22,2					02.3511.50.12
22,5 x 9,00	12 R22,5; 12/70 R22,5; 285/60 R22,5; 295/60 R22,5; 305/60 R22,5; 315/60 R22,5; 285/70 R22,5; 295/70 R22,5; 305/70 R22,5; 315/70 R22,5; 285/75 R22,5; 295/75 R22,5; 305/75 R22,5; 315/75 R22,5; 285/80 R22,5; 295/80 R22,5; 305/80 R22,5; 315/80 R22,5	brillant	153	175	32	4250	25,4	281/335/10	22	yes	Truck & Trailer/semitrailer	02.3511.51.12
					26		25,6					02.3511.52.12
		highly polished	153	175	32	4250	25,4	281/335/10	22	yes	Truck & Trailer/semitrailer	02.3511.53.12
					26		25,6					02.3511.54.12
22,5 x 8,25	11 R22,5; 12 R22,5; 265/60 R22,5; 285/60 R22,5; 255/70 R22,5; 265/70 R22,5; 275/70 R22,5; 285/70 R22,5; 295/70 R22,5; 305/70 R22,5; 255/75 R22,5; 265/75 R22,5; 275/75 R22,5; 285/75 R22,5; 295/75 R22,5; 305/75 R22,5; 255/80 R22,5; 265/80 R22,5; 275/80 R22,5; 285/80 R22,5; 295/80 R22,5; 305/80 R22,5	brillant	145	167	32	3650	22,9	281/335/10	22	yes	Trailer/semitrailer	02.3511.55.12
					26		23,1					02.3511.56.12
		highly polished	145	167	32	3650	22,9	281/335/10	22	yes	Trailer/semitrailer	02.3511.57.12
					26		23,1					02.3511.58.12
17,5 x 6,75	9,5 R17,5; 10 R17,5; 205/75 R17,5; 215/75 R17,5; 225/75 R17,5; 235/75 R17,5; 245/70 R17,5; 245/75 R17,5	brillant	117	138	26	3000	14,8	176/225/10	20	yes	Trailer/semitrailer	02.3511.59.12
		highly polished	117	138	26	3000	14,8	176/225/10	20	yes	Trailer/semitrailer	02.3511.60.12

## NUTS FOR WHEEL FASTENING (WHEEL NUTS WITH CORROSION-RESISTANT DACRORNET COATING)

Nut for aluminium + steel (silver)	ET 0 and ET 120	M 22 x 1,5/27 mm high	26	05.260.54.10.0
Shaft nut, short (silver)	Single tyres	M 22 x 1,5/39 mm high	32	05.260.54.21.1
Shaft nut, long (silver)	Twin tyres	M 22 x 1,5/62 mm high	32	05.260.54.14.1

## NUTS FOR WHEEL FASTENING/STANDARD VALVE

Shaft nut, short, Scania	Individual tyres	7/8", 11 BSF	32	02.5219.39.10
Shaft nut, long, Scania	Twin tyres	7/8", 11 BSF	32	02.5219.40.10
Standard valve	for all wheel sizes, straight version			02.4321.05.00